Applicant(s): P. Bonutti Application No.: 10/078,030

Examiner: G. Jackson

Amendments to the Claims

1. (Currently Amended) An apparatus for use in positioning an anchor member relative to body tissue, the apparatus comprising

a tubular member through which the anchor member is movable and including an end portion operable between a closed condition blocking movement of the anchor member through the end portion into the body tissue and an open condition in which the end portion is ineffective to block movement of the anchor member into the body tissue, and

a pusher member which is at least partially disposed in and is movable relative to the tubular member to move the anchor member relative to the tubular member.

wherein the end portion has a pointed end in the closed condition, the <u>pointed</u> end portion configured and dimensioned for piercing an imperforate surface on the body tissue.

2.-10. (Cancelled)

11. (Previously Presented) A method of positioning an anchor member relative to body tissue, the method comprising the steps of

positioning an end portion of a tubular member relative to body tissue with the end portion of the tubular member in a closed condition at least partially blocking a passage in the tubular member.

moving the tubular member into body tissue by piercing the body tissue with the end portion of the tubular member,

moving an anchor member along the passage in the tubular member with a suture disposed in engagement with the anchor member,

operating the end portion of the tubular member from the closed condition to an open condition, and

moving the anchor member through the end portion of the tubular member into the body tissue while the end portion of the tubular member is in the open condition.

e.

Applicant(s): P. Bonutti Application No.: 10/078,030 Examiner: G. Jackson

12.-64. (Cancelled)

65. (Previously Presented) The apparatus of claim 1 further comprising indicia disposed on the end portion of the tubular member, the indicia indicating a depth of insertion of the end portion into body tissue as the body tissue is pierced by the pointed end.

66. (Currently Amended) The apparatus of claim 1 An apparatus for use in positioning an anchor member relative to body tissue, the apparatus comprising:

a tubular member through which the anchor member is movable and including an end portion operable between a closed condition blocking movement of the anchor member through the end portion into the body tissue and an open condition in which the end portion is ineffective to block movement of the anchor member into the body tissue, wherein the end portion of the tubular member comprises including a plurality of segments, each of the segments including having an inner surface, an outer surface and a plurality of side surfaces which extend between the inner and outer surfaces, the side surfaces on each of the segments being disposed adjacent to side surfaces on adjacent segments when the end portion of the tubular member is in the closed condition, and

a pusher member which is at least partially disposed in and is movable relative to the tubular member to move the anchor member relative to the tubular member.

wherein the outer surfaces on of the segments cooperate to form the pointed end of the tubular member when the end portion is in the closed position the end portion having a pointed end in the closed condition, the pointed end configured and dimensioned for piercing an imperforate surface on the body tissue.

67. (Previously Presented) The apparatus of claims 66 wherein the tubular member includes a sheath through which the anchor member is movable, the sheath resiliently expandable under the influence of force transmitted from the anchor member to the sheath as the anchor member is

Applicant(s): P. Bonutti Application No.: 10/078,030 Examiner: G. Jackson

Examines: O. Jacks

moved through the tubular member by the pusher member.

68. (Previously Presented) The apparatus of claim 1 wherein the tubular member includes a sheath through which the anchor member is movable, the sheath resiliently expandable under the influence of force transmitted from the anchor member to the sheath as the anchor member is moved through the tubular member by the pusher member.

69. (Currently Amended) The apparatus of claim 68 wherein the tubular member further comprises an An apparatus for use in positioning an anchor member relative to body tissue, the apparatus comprising:

a tubular member through which the anchor member is movable and including an end portion operable between a closed condition blocking movement of the anchor member through the end portion into the body tissue and an open condition in which the end portion is ineffective to block movement of the anchor member into the body tissue, the tubular member including a sheath through which the anchor member is movable, and an array of wires which extend along an inner side of the sheath; and

a pusher member which is at least partially disposed in and is movable relative to the tubular member to move the anchor member relative to the tubular member, the sheath resiliently expandable under the influence of force transmitted from the anchor member to the sheath as the anchor member is moved through the tubular member by the pusher member,

wherein the end portion has a pointed end in the closed condition, the pointed end configured and dimensioned for piercing an imperforate surface on the body tissue.

70. (Previously Presented) The apparatus of claim 69 wherein the array of wires blocks engagement of the anchor member with the sheath during movement of the anchor member relative to at least a portion of the tubular member.

FKGGBB MIAMI

Applicant(s): P. Bonutti Application No.: 10/078,030 Examiner: G. Jackson

71. (Previously Presented) The apparatus of claim 69 wherein the pointed end of the tubular member is formed by the sheath and the array of wires.

72. (Previously Presented) The apparatus of claim I wherein the closed condition of the end portion of the tubular member blocks movement of the body tissue through the end portion into the tubular member.

73. (Previously Presented) The method of claim 11 wherein the tubular member includes a plurality of wires which extend along a passage in the tubular member.

74. (Previously Presented) The method of claim 73 wherein moving the anchor member along a passage in the tubular member includes sliding the anchor member along the wires and moving the anchor member out of the passage in the tubular member into the body tissue.

75. (Previously Presented) The method of claim 11 further comprising expanding at least a portion of the passage in the tubular member by transmitting force from a leading end portion of the anchor member to the tubular member while moving the anchor member along the passage in the tubular member.

76. (Previously Presented) The method of claim 11 wherein the step of piercing the body tissue includes forming an opening in the body tissue at a location which is free of naturally occurring openings.

77. (Previously Presented) The method of claim 11 further comprising expanding at least a portion of the passage in the tubular member by resiliently stretching material which forms at least a portion of the tubular member.

78. (Previously Presented) The method of claim 11 further comprising moving segments of

Applicant(s): P. Bonutti Application No.: 10/078,030 Examiner: G. Jackson

the end portion of tubular member which pierced the body tissue from an closed position in which portions of the segments of the end portion of the tubular member are disposed in

engagement with each other to an open position in which the portions of the segments of the end

portion of the tubular member are spaced apart from each other.

79. (Previously Presented) The method of claim 11 further including the steps of covering indicia on the tubular member with body tissue as the tubular member is inserted into the body tissue, and interrupting insertion of the tubular member into body tissue in response to covering of indicia corresponding to a desired depth of insertion of the tubular member into body tissue.